

Xinglun Rope. Leading the World!

SEAKEEPER™ UHMWPE SBA ROPE

- Dry & Wet Conditions:
Wet Strength Equals Dry Strength
- Non-Rotating and Anti-Kinking
- Easy to Handle, Inspect and Repair
- Longer Service Life

CHARACTERISTICS

- Material: UHMWPE
- Construction: 8/12 Strand
- Melting Point: 150°C
- Elongation: 3-4%
- Abrasion Resistance
- Chemical Resistance
- UV Resistance
- Water Absorption: None

SEAKEEPER™ PP/PES SBA ROPE

- Abrasion Resistance
- Chemical Resistance
- UV Resistance
- Dry & Wet Conditions:
Wet Strength Equals Dry Strength
- Excellent Shock Absorption

CHARACTERISTICS

- Material: High Tenacity PP and Polyester Fibers
- Construction: 3/8/12 Strand
- Melting Point: 165°C/260°C
- Elongation: 3-4%
- Water Absorption: None

MSRL™ PILOT LADDER

MSRL Pilot Ladder with Manila side rope is widely used as descending ladder in ship (eg containers). It is finished with eye on top for easy mounting, an ideal product for general purpose and different sizes are available.

MSRL™ EMBARKATION LADDER

The MSRL embarkation ladder is used on merchant vessels to embark survival crafts. The four steps at the bottom of pilot ladder and lifeboat ladder are made of rubber.

Get in touch with us

XINGLUN ROPE (EUROPE) Co LTD

M +357 95166423 T +357 25 053680
e s.athanasiadis@xlrope.eu / sales@xlrope.eu
23 lapetou Street, Ayios Athanasios Industrial Area
4101 Limassol, Cyprus



XINGLUN ROPE
(EUROPE) CO LTD

